

Live Fire Test Report for the SU-231A/PEQ



TP/JXNLM/C11/0541

USSOCOM Weapons Accessories Engineering Section JOINT SPECIAL OPERATIONS RESPONSE DEPARTMENT CRANE DIVISION, NAVAL SURFACE WARFARE CENTER

DISTRIBUTION AUTHORIZED TO U.S. GOVERNMENT AGENCIES ONLY. OTHER REQUESTS FOR THIS DOCUMENT SHALL BE REFERRED TO COMMANDER, CODE JSOP, NAVAL SURFACE WARFARE CENTER, 300 HIGHWAY 361, CRANE, IN 47522-5001

SIGNATURE PAGE

Prepared By:	
(b)(6)	2-23-11
	Date
USSOCOM Weapons Accessories Engineering – McCrane Division, Naval Surface Warfare Center	echanical Engineer
Reviewed By:	
(b)(6)	23 Feb 11 Date
USSOCOM Weapons Accessories Engineering – Mo Crane Division, Naval Surface Warfare Center	echanical Engineer
Reviewed By:	
(b)(6)	23Fcs 2\$11 Date
VIII	
USSOCOM Weapons Accessories Engineering Sect Crane Division, Naval Surface Warfare Center	ion Manager/JXNLM
Approved By:	
(b)(6)	23 Fes 2411
	Date

Joint Weapons Engineering Acting Branch Manager/JXNL Crane Division, Naval Surface Warfare Center

TABLE OF CONTENTS

SIGNATURE PAGE	1
TABLE OF CONTENTS	2
1. Introduction	
2. Purpose	
3. System Descriptions	
4. Host Weapons	
5. Data and Findings	
5.1. Data Requirements	
5.2 Live Fire Test Findings	
6. Engineering Design Changes	
7. Conclusion	
7. Conclusion	4

TEST REPORT FOR THE LIVE FIRE TESTING OF THE SU-231A/PQ

1. Introduction

This Test Report outlines results from the Live Fire Testing (LFT) of SU-231A/PEQ.

2. Purpose

The SU-231A/PEQ (EXPS) will be be fielded as a phased replacement for the SU-231/PEQ. Weapons Accessories Engineering (WPNAC) has tested the EOTech XPS weapon sight in conjunction with several live fire tests in the past year to verify the suitability of the EXPS in place of the SU-231/PEQ

3. System Descriptions

The XPS is a smaller, more rugged version of the SU-231/PEQ, offering the same functionality. The XPS utilizes a single CR123 battery transversely aligned to the barrel of the weapon vs. the SU-231/PEQ, which has two CR123 batteries co-axially aligned with the barrel. There are two differences between the XPS and the EXPS; otherwise the sights are considered to be the same. The XPS has the control buttons on the back of the sight like the original SU-231/PEQ, whereas the EXPS is configured with the controls on the side to provide easier function manipulation while the sight is used in conjunction with a magnifying optic. Also, the XPS has a screw mount while the EXPS is designed with a throw lever mount.

4. Host Weapons

The host weapon utilized for the XPS verification testing was the MK-17 SOF Combat Assault Rifle - Heavy.


5. Data and Findings

5.1. Data Requirements

In order to verify the suitability of the EXPS as a phased replacement for the SU-231/PEQ, the XPS was tested in conjunction with several other WPNAC live fire tests for accessory endurance as a secondary component to those tests. Initial testing began in March 2010, and all tests were complete by May 2010. This testing provided endurance information on five XPS sights out to 15,600 rounds each on the MK-17. Any performance issues with the XPS during testing were recorded on the test data sheets.


5.2 Live Fire Test Findings

The only endurance issue identified on the XPS while fired on the MK-17 was



any problems.

6. Engineering Design Changes



7. Conclusion

The XPS performed acceptably throughout live fire testing. As a result, the EXPS has been accepted as a suitable replacement for the SU-231/PEQ.